

UBBL19 - UBBL22

Technical Datasheet

**** Preliminary - Contact Ultralife for Availability ****



**2.4Ah Li-ION
Rechargeable Batteries
3.6V – 14.4V**

Ultralife Part Number	Description	MAX Dimensions (mm) (Thickness x Width x Length)	Voltage Range	Nominal Voltage	Nominal Capacity	Max Discharge	Approximate Weight
UBBL19	3.6V, 2.4Ah Li-Ion Rechargeable Battery	23.2 x 19.1 x 67.0	3.0 to 4.2V	3.6V	2.4Ah	2500mA	50g
UBBL20	7.2V, 2.4Ah Li-Ion Rechargeable Battery	21.0 x 38.0 x 67.0	6.0 to 8.4V	7.2V	2.4Ah	2500mA	96g
UBBL21	10.8V, 2.4Ah Li-Ion Rechargeable Battery	22.0 x 56.5 x 67.0	9.0 to 12.6V	10.8V	2.4Ah	2500mA	143g
UBBL22	14.4V, 2.4Ah Li-Ion Rechargeable Battery	22.0 x 75.0 x 67.0	12.0 to 16.8V	14.4V	2.4Ah	2500mA	192g

Cycle Life: 300 Cycles @ C/5 to 80%

Operating Temperatures

- Charge: 0° to +45°C
- Discharge: -20° to +60°C

Storage Temperature: -20° to +50°C

Self Discharge: <10% per month

Exterior: PVC Shrink

Termination:

- UBBLXX-FL: 22AWG
- UBBLXX-C1: Connector: JST VHR-2N.

FEATURES/BENEFITS

- Off-the-shelf convenience
- Wire or connector terminals
- Full circuit protection
- Meets all UN transportation testing
- Wide operating temperature range
- No memory effect
- Lightweight

APPLICATIONS

- Portable electronics
- Hand-held devices
- Medical equipment
- Back-up power